

## INSTALLATION RECOMMENDATIONS FOR DELMO SPEED 73-87 CHEVY C10 EXTERIOR DOOR HANDLES

### Included Parts List:

- (1) Driver Side Door Handle
- (1) Passenger Side Door Handle
- (2) Buttons
- (2) Clear Gasket Sets
- (2) Roll Pins
- (2) Cam return springs
- (1) Handle cutout template
- (4 sets) Handle hardware *Note: flat washers may not fit on all vehicles depending on the outer door seam.*


**\*\*Important Note: Due to the age of the vehicle and wear & tear of daily use, some parts may require extra adjustment or extra steps may be required to insure correct fitment.\*\***

**Step 1** - Remove interior door panel :

**Step 2** - For easier access remove interior door handle clip and rod (Pic 1 & 2 )



Pic 1



Pic 2 - clip

**Step 3** - Remove exterior door handle clip and rod in order to remove handle

**Step 4** - Remove factory roll pin from factory door handle (Pic 3) in order remove lever.



Pic 3 - roll pin


**Step 5** - In some cases it might be necessary to trim part of the factory lever for clearance. See shaded area on (Pic 4)

**Step 6** - Using the new roll pin and spring provided, install the factory lever into the new billet handle.



Pic 4

**Step 7** - Using the template provided, remove material from the door skin to allow fitment of our new designed larger button area. This can be accomplished with a rat tail file or Dremel tool. See arrows on (Pic 5)




Pic 5 - template

**Step 8** - Stick clear gaskets provided to the back of billet handle (Pic 6)

**Step 9** - After installing the rod thru the factory lever, Install the new billet handle and attach the rod to the latch assembly.

**Step 10** - Test handles for proper operation prior to installing door panels and trim.



Pic 6- clear gasket